Inspection Report Checklist

TYPE (SELECT BELOW):

TETHER POINT ☐ STORAGE ☐

TOOL LANYARD ☐ OTHER ☐

ANCHOR POINT ☐

PRODUCT CODE:

SERIAL NUMBER:

COMMENTS:

AREA OF INSPECTION	PASS / FAIL	COMMENTS
WEBBING / CORD Inspect for cuts, abrasion, frays, burns, soiling, discolouring	PASS ☐ FAIL ☐	
STITCHING Inspect for wear, frays and cuts	PASS ☐ FAIL ☐	
HARDWARE (Quick Clips, Carabiners, D Rings and other metal componentry) Inspect for distortion, cracks, sharp edges, corrosion and proper operation	PASS ☐ FAIL ☐	
LABELS Inspect for legibility and ensure labels are securely attached	PASS ☐ FAIL ☐	
BASE FABRIC (Storage, Bags and Pouches) Inspect for wear, cuts, abrasions and breakdown in structural stitching	PASS ☐ FAIL ☐	
INSPECTION SUMMARY: PASS ☐ FAIL ☐	INSPECTED BY: DATE OF INSPECTION:	SIGNATURE:

Find out more at:
neverletgo.com

NLG

CARING FOR YOUR NLG SAFETY EQUIPMENT

After use, clean the equipment of dirt, corrosives, or contaminants and store in a clean and dry environment, free from fumes or corrosive elements. Taking care of your safety equipment will ensure it works effectively and will extend its service life.

CLEANING INSTRUCTIONS

- Clean off the surface dirt with a water-dampened wipe.
- Dip the wipe in a mild solution of water, soap, or detergent. Work it up into a thick lather and clean the item.
- Wipe with a clean cloth and hang to dry away from excessive heat, steam, or sunlight.